

# TOUGH QUEEN

BOND OF QUALITY

LUXURY ACRYLIC POLYMER EMULSION  
(INTERIOR & EXTERIOR)



[ TECHNICAL DATA SHEET ]

**V**<sup>TM</sup>  
TEXTURE  
COATINGS



Texture Coatings, Plot No. E-91, In Additional Patalganga Industrial Area, Patalganga - 410207

✉ [info@texturecoatings.in](mailto:info@texturecoatings.in)

☎ +91 8692888888

🌐 [www.texturecoatings.in](http://www.texturecoatings.in)

# TOUGH QUEEN

BOND OF QUALITY

LUXURY ACRYLIC POLYMER EMULSION  
(INTERIOR & EXTERIOR)

## DESCRIPTION

TEXTURE COATINGS TOUGHQUEEN IS A LUXURY ACRYLIC POLYMER EMULSION TO GIVE YOUR WALLS AN EXUBERANT LUXURIOUS FINISH.



## KEY FEATURES



EASY TO  
CLEAN



BRUSH/ROLLER  
APPLICATION



EXCELLENT  
COVERAGE



ANTI  
ALGAL/FUNGAL



POLYMER  
ADHESION



## BOND OF QUALITY

LUXURY ACRYLIC POLYMER EMULSION  
(INTERIOR & EXTERIOR)

### DIRECTIONS FOR USE

#### DIRECTION FOR USE

**Cleaning:** Sand the surface with sand paper 180 to ensure that the surface is clean, dry, free from all the loose particles, cracker or flaked paint, dust, grease, dirt, wax, mould, fungal growth, etc. Before application. Wipe clean the surface with a damp cloth after the process.

**Primer: (Initial Coat)** Apply 1 coat of Texture Coatings ToughSeal wall sealer (WT). Allow a drying time of 6-8 Hours.

**Putty:** Apply 2 coats of Texture Coatings ToughCoat premium stucco polymer based acrylic putty to cover wall undulations. Allow a drying time of 6 – 8 hours. Sand the surface with Sand Paper 320 and wipe clean to achieve a silky smooth shiny surface.

**Primer: ( Final Coat)** Apply a coat of Texture Coatings ToughSeal wall sealer (WT). Allow a drying time of 6-8 Hours.

**Dilution:** Use only clean portable water as per the table below:

Sr No.	Shade Type	Dilution Level (%)
1	White & Pastel	40 to 50
2	Deep & Medium	25 to 30
3	Vibrant & Extra Dark	10 to 20

**Top coat:** Apply 2 coats of Texture Coatings ToughQueen Internal luxury Acrylic Polymer Emulsion with a drying time interval of 6 – 8 hours between the 2 coats. Use high density polyester rollers / microfiber rollers for optimum results.



BOND OF QUALITY

LUXURY ACRYLIC POLYMER EMULSION  
(INTERIOR & EXTERIOR)

## SAFETY MEASURES

Do not over thin the material.

Store the bag in a cool, dry place.

No added Lead, Mercury or Chromium compounds.

Keep out of reach of children and away from eatables.

May be harmful if swallowed. In case of ingestion, seek immediate medical attention.

It is recommended to wear suitable nose pad during sanding and surface preparation to avoid dust inhalation.

In case of skin contact immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists.

Wear eye protection during application. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Kindly refer to the technical data sheet for **ToughQueen** which gives detailed information on safety measures while handling the paint.

## PRECAUTIONS



### Temperature

Do not apply when temperature is less than 10°C



### Mixing

Please mix the material well before use



Texture Coatings, Plot No. E-91, In Additional Patalganga Industrial Area, Patalganga - 410207

 [info@texturecoatings.in](mailto:info@texturecoatings.in)

 +91 8692888888

 [www.texturecoatings.in](http://www.texturecoatings.in)