

TOUGH *star*

BOND OF QUALITY


STANDARD ACRYLIC POLYMER EMULSION
(INTERIOR & EXTERIOR)





[TECHNICAL DATA SHEET]



Texture Coatings, Plot No. E-91, In Additional Patalganga Industrial Area, Patalganga - 410207

 info@texturecoatings.in

 +91 8692888888

 www.texturecoatings.in

TOUGHstar[★]

BOND OF QUALITY

STANDARD ACRYLIC POLYMER EMULSION
(INTERIOR & EXTERIOR)

DESCRIPTION

TEXTURE COATINGS TOUGHSTAR IS AN ECONOMIC YET VERY DURABLE STANDARD ACRYLIC POLYMER EMULSION TO GIVE YOUR WALLS DESIRED FINISH.



KEY FEATURES



**EASY TO
CLEAN**



**BRUSH/SPRAY
APPLICATION**



**BEST IN
CLASS
COVERAGE**



**MATTE
FINISH**



**POLYMER
ADHESION**

TOUGHstar

BOND OF QUALITY

STANDARD ACRYLIC POLYMER EMULSION
(INTERIOR & EXTERIOR)

DIRECTIONS FOR USE

DIRECTION FOR USE

Cleaning: Sand the surface with sand paper 180 to ensure that the surface is clean, dry, free from all the loose particles, cracker or flaked paint, dust, grease, dirt, wax, mould, fungal growth, etc. Before application. Wipe clean the surface with a damp cloth after the process.

Primer: (Initial Coat) Apply 1 coat of Texture Coatings ToughPrime wall primer (WT). Allow a drying time of 6-8 Hours.

Putty: Apply 2 coats of Texture Coatings ToughCoat premium stucco polymer based acrylic putty to cover wall undulations. Allow a drying time of 4 – 6 hours. Sand the surface with Sand Paper 320 and wipe clean to achieve a silky smooth shiny surface.

Primer: (Final Coat) Apply a coat of Texture Coatings ToughPrime wall primer (WT). Allow a drying time of 6-8 Hours.

Dilution: Use only clean portable water as per the table below:

Sr No.	Shade Type	Dilution Level (%)
1	White & Pastel	30 to 40
2	Deep & Medium	20 to 25
3	Vibrant & Extra Dark	10 to 15

Top coat: Apply 2 coats of Texture Coatings ToughStar Internal Standard Acrylic Polymer Emulsion with a drying time interval of 6 – 8 hours between the 2 coats. Use high density polyester rollers / microfiber rollers for optimum results.

TOUGH *star*

BOND OF QUALITY

STANDARD ACRYLIC POLYMER EMULSION
(INTERIOR & EXTERIOR)

SAFETY MEASURES

Do not over thin the material.

Store the can/drum in a cool, dry place.

No added Lead, Mercury or Chromium compounds.

Keep out of reach of children and away from eatables.

May be harmful if swallowed. In case of ingestion, seek immediate medical attention.

It is recommended to wear suitable nose pad during sanding and surface preparation to avoid dust inhalation.

In case of skin contact immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists.

Wear eye protection during application. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Kindly refer to the technical data sheet for **ToughStar** which gives detailed information on safety measures while handling the paint.

PRECAUTIONS



Temperature

Do not apply when temperature is less than 10°C



Mixing

Please mix the material well before use



Texture Coatings, Plot No. E-91, In Additional Patalganga Industrial Area, Patalganga - 410207

 info@texturecoatings.in

 +91 8692888888

 www.texturecoatings.in