

# **TOUGH** **STRETCH** **BOND OF QUALITY**


**ELASTOMERIC WATERPROOF  
ACRYLIC POLYMER EMULSION  
(EXTERIOR & INTERIOR)**




**[ TECHNICAL DATA SHEET ]**



Texture Coatings, Plot No. E-91, In Additional Patalganga Industrial Area, Patalganga - 410207

 [info@texturecoatings.in](mailto:info@texturecoatings.in)

 +91 8692888888

 [www.texturecoatings.in](http://www.texturecoatings.in)

# TOUGH STRETCH

## BOND OF QUALITY


ELASTOMERIC WATERPROOF ACRYLIC POLYMER EMULSION  
(EXTERIOR & INTERIOR)

### DESCRIPTION

TOUGHSTRETCH IS A PREMIUM ELASTOMERIC POLYMER ACRYLIC EMULSION SPECIALLY FORMULATED TO STRETCH AND BRIDGE HAIRLINE CRACKS AND PROVIDES PROTECTION FROM WATER PENETRATION.



### KEY FEATURES



**BRIDGES HAIRLINE  
CRACKS**



**BRUSH/ROLLER  
APPLICATION**



**EXCELLENT  
COVERAGE**



**ANTI  
ALGAL/FUNGAL**



**POLYMER  
ADHESION**

# TOUGH STRETCH

## BOND OF QUALITY

ELASTOMERIC WATERPROOF ACRYLIC POLYMER EMULSION  
(EXTERIOR & INTERIOR)

### DIRECTIONS FOR USE

#### DIRECTION FOR USE

**Plaster:** New masonry surfaces must be allowed to cure completely. It is recommended to allow 28 days as the curing time for new masonry surfaces.

**Cleaning:** Clean the surface thoroughly with a wire brush to ensure the surface is clean, dry, free from all the loose particles, cracked or flaked paint, dust, grease, dirt, wax, mould and fungal growth, etc.

**Filling:** Surface impurities such as holes, dents, fine cracks are to be filled with crack filling paste /shrink-free paste.

**Sealer:** It is important to completely cure a freshly plastered surface. Apply a coat of Texture Coatings ToughSeal multipurpose wall sealer (WT). Allow a drying time of 6 - 8 Hours.

**Dilution:** Use only clean portable water to dilute ToughStretch as per the table below:

| Sr No. | Shade Type     | Dilution Level (%) |
|--------|----------------|--------------------|
| 1      | White & Pastel | 30 to 40           |
| 2      | Deep & Medium  | 10 to 20           |
| 3      | Extra Dark     | 5 to 10            |

**Top coat:** Apply 2 coats of Texture Coatings ToughStretch paint with a drying time interval of 6 – 8 hours between the 2 coats.

**Do Not Apply** on surfaces that experience dampness or have seepage issues.

# TOUGH STRETCH BOND OF QUALITY

ELASTOMERIC WATERPROOF ACRYLIC POLYMER EMULSION  
(EXTERIOR & INTERIOR)

## SAFETY MEASURES

Do not over thin the material.

Store the can/drum in a cool, dry place.

No added Lead, Mercury or Chromium compounds.

Keep out of reach of children and away from eatables.

May be harmful if swallowed. In case of ingestion, seek immediate medical attention.

It is recommended to wear suitable nose pad during sanding and surface preparation to avoid dust inhalation.

In case of skin contact immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists.

Wear eye protection during application. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Kindly refer to the technical data sheet for **ToughStretch** which gives detailed information on safety measures while handling the paint.

## PRECAUTIONS



### Temperature

Do not apply when temperature is less than 10°C



### Mixing

Please mix the material well before use



Texture Coatings, Plot No. E-91, In Additional Patalganga Industrial Area, Patalganga - 410207

 [info@texturecoatings.in](mailto:info@texturecoatings.in)

 +91 8692888888

 [www.texturecoatings.in](http://www.texturecoatings.in)